

Features

- Visible Light Facial Recognition
- Anti-spoofing algorithm against most of color and B/W photos, videos attack and 3D mask attack
- 2.8-inch Tocuh Screen
- Supplement lighting with adjustable brightness
- Exquisite and compact, easy to install. Support desktop and wall install
- Support Multiple Language

Visible Light Facial Recognition Embedded



Proactive Facia Recognition



New Height of Anti-Spoofing



Recognitio




Wide Pose Angle Acceptance



Better Hygiene

Recognition distance 2m long and extra wide angle recognition


The recognition distance has been greatly extended to 2m meters long, which significantly improves maximum traffic rate. While most of the algorithms only support +/-15° of detectable face angle, MiniTA doubles the detection angle in terms of head rotation and tilt to +/- 30°.



Specifications:

| Display | 2.8-inch Touch Screen |
|------------------------|---------------------------------------------------------------------------------------------------------------------|
| Face Capacity | 800 |
| User Capacity | 800 |
| Transactions | 150,000 |
| Operation System | Linux |
| Standard Functions | ADMS, T9 Input, DST, Camera, 9 digit user ID, Work Code, Self-service Query, Schedule Bell, Automatic Status Switch |
| Hardware | 900MHZ Dual Core CPU Memory 512MB RAM / 512MB ROM 2MP WDR Low Light Camera Adjustable Light Brightness LED |
| Communication | WiFi |
| Operation System | Linux |
| Face Recongntion Speed | ≤1s |
| Biometrics Algorithms | ZKFace VX5.8 |
| Power Supply | 5V / 2A |
| Working Humidity | 10%-90% |
| Working Temperature | 0 °C- 45 °C |
| Dimensios(W*H*D) | 100*100.2*23.7mm |
| Supported Software | easyTime Pro |

Configuration



Dimensions(mm)



